



A Division of Cisco Systems, Inc.

Linksys Phone Adapter Configuration

[Info](#) |
 [System](#) |
 [SIP](#) |
 [Provisioning](#) |
 [Regional](#) |
 Line 1 |
 [PSTN Line](#) |
 [User 1](#) |
 [PSTN User](#) |
 [User Login](#) |
 [basic](#) |
 advanced

Line Enable: yes ▼

Streaming Audio Server (SAS)

SAS Enable: no ▼

SAS DLG Refresh Intvl: 30

SAS Inbound RTP Sink:

NAT Settings

NAT Mapping Enable: no ▼

NAT Keep Alive Enable: no ▼

NAT Keep Alive Msg: \$NOTIFY

NAT Keep Alive Dest: \$PROXY

Network Settings

SIP TOS/DiffServ Value: 0x68

Network Jitter Level: high ▼

RTP TOS/DiffServ Value: 0xb8

Jitter Buffer Adjustment: up and down ▼

SIP Settings

SIP Port: 5060

SIP 100REL Enable: no ▼

EXT SIP Port:

Auth Resync-Reboot: yes ▼

SIP Proxy-Require:

SIP Remote-Party-ID: yes ▼

SIP GUID: no ▼

SIP Debug Option: none ▼

RTP Log Intvl:

Restrict Source IP:

0
 Referor Bye Delay: 4
 Referee Bye Delay: 0
 Sticky 183: no ▼

Call Feature Settings

Blind Attn-Xfer Enable: no ▼
 Xfer When Hangup Conf: yes ▼

Proxy and Registration

Proxy: 192.168.0.6
 Outbound Proxy:
 Register: yes ▼
 Register Expires: 3600
 Use DNS SRV: no ▼
 Proxy Fallback Intvl: 3600
 Voice Mail Server:

Subscriber Information

Display Name: 9254919
 Password: *****
 Auth ID: 1188
 Mini Certificate:
 SRTP Private Key:

Supplementary Service Subscription

Call Waiting Serv: yes ▼
 Block ANC Serv: yes ▼
 Cfwd All Serv: yes ▼

no ▼
 Refer Target Bye Delay: 0
 Refer-To Target Contact: no ▼

MOH Server:

Use Outbound Proxy: no ▼
 Use OB Proxy In Dialog: no ▼
 Make Call Without Reg: yes ▼
 Ans Call Without Reg: yes ▼
 DNS SRV Auto Prefix: no ▼
 Proxy Redundancy Method: Normal ▼
 Mailbox Subscribe Expires: 2147483647

User ID: 1188
 Use Auth ID: yes ▼

Block CID Serv: yes ▼
 Dist Ring Serv: yes ▼
 Cfwd Busy Serv: yes ▼

Cfwd No Ans Serv: yes ▼
 Cfwd Last Serv: yes ▼
 Accept Last Serv: yes ▼
 CID Serv: yes ▼
 Call Return Serv: yes ▼
 Call Back Serv: yes ▼
 Three Way Conf Serv: yes ▼
 Unattn Transfer Serv: yes ▼
 VMWI Serv: yes ▼
 Secure Call Serv: yes ▼
 Feature Dial Serv: yes ▼

Audio Configuration

Preferred Codec: G711u ▼
 Use Pref Codec Only: no ▼
 G729a Enable: yes ▼
 G723 Enable: yes ▼
 G726-16 Enable: yes ▼
 G726-24 Enable: yes ▼
 G726-32 Enable: yes ▼
 G726-40 Enable: yes ▼
 DTMF Process INFO: yes ▼
 DTMF Process AVT: yes ▼
 DTMF Tx Method: Auto ▼
 FAX Process NSE: yes ▼
 FAX Disable ECAN: no ▼
 Symmetric RTP: yes ▼

Gateway Accounts

Cfwd Sel Serv: yes ▼
 Block Last Serv: yes ▼
 DND Serv: yes ▼
 CWCID Serv: yes ▼
 Call Redial Serv: yes ▼
 Three Way Call Serv: yes ▼
 Attn Transfer Serv: yes ▼
 MWI Serv: yes ▼
 Speed Dial Serv: yes ▼
 Referral Serv: yes ▼
 Service Announcement Serv: no ▼

Silence Supp Enable: no ▼
 Silence Threshold: medium ▼
 Echo Canc Enable: yes ▼
 Echo Canc Adapt Enable: yes ▼
 Echo Supp Enable: yes ▼
 FAX CED Detect Enable: yes ▼
 FAX CNG Detect Enable: yes ▼
 FAX Passthru Codec: G711u ▼
 FAX Codec Symmetric: yes ▼
 FAX Passthru Method: NSE ▼
 DTMF Tx Mode: Strict ▼
 Hook Flash Tx Method: None ▼
 Release Unused Codec: yes ▼

Gateway 1: 192.168.0.6
 GW1 Auth ID: 1188
 Gateway 2:
 GW2 Auth ID:
 Gateway 3:
 GW3 Auth ID:
 Gateway 4:
 GW4 Auth ID:

GW1 NAT Mapping Enable: no ▼
 GW1 Password: *****
 GW2 NAT Mapping Enable: no ▼
 GW2 Password:
 GW3 NAT Mapping Enable: no ▼
 GW3 Password:
 GW4 NAT Mapping Enable: no ▼
 GW4 Password:

VoIP Fallback To PSTN

Auto PSTN Fallback: yes ▼

Dial Plan

Dial Plan: (*xx|[3469]11|0|00|[2-9]xxxxxx|1xxx[2-9]xxxxxxS0|xxxxxxxxxxxxx.)

Enable IP Dialing: yes ▼ Emergency Number:

FXS Port Polarity Configuration

Idle Polarity: Forward ▼ Caller Conn Polarity: Forward ▼
 Callee Conn Polarity: Forward ▼

Undo All Changes

Submit All Changes

[User Login](#) [basic](#) | [advanced](#)