



Linksys Phone Adapter Configuration

[Info](#) | [System](#) | [SIP](#) | [Provisioning](#) | [Regional](#) | [Line 1](#) | [PSTN Line](#) | [User 1](#) | **PSTN User** | [User Login](#) | [basic](#) | [advanced](#)

PSTN-To-VoIP Selective Call Forward Settings

Cfwd Sel1 Caller:

Cfwd Sel1 Dest:

Cfwd Sel2 Caller:

Cfwd Sel2 Dest:

Cfwd Sel3 Caller:

Cfwd Sel3 Dest:

Cfwd Sel4 Caller:

Cfwd Sel4 Dest:

Cfwd Sel5 Caller:

Cfwd Sel5 Dest:

Cfwd Sel6 Caller:

Cfwd Sel6 Dest:

Cfwd Sel7 Caller:

Cfwd Sel7 Dest:

Cfwd Sel8 Caller:

Cfwd Sel8 Dest:

PSTN-To-VoIP Speed Dial Settings

Speed Dial 2:

Speed Dial 3:

Speed Dial 4:

Speed Dial 5:

Speed Dial 6:

Speed Dial 7:

Speed Dial 8:

Speed Dial 9:

PSTN Ring Thru Line 1 Distinctive Ring Settings

Ring1 Caller:

Ring2 Caller:

Ring3 Caller:

Ring4 Caller:

Ring5 Caller:

Ring7 Caller:

Ring6 Caller:

Ring8 Caller:

PSTN Ring Thru Line 1 Ring Settings

Default Ring: 1 ▼

Undo All Changes

Submit All Changes

[User Login](#) [basic](#) | advanced

Copyright © 2003-2005 Sipura Technology. All Rights Reserved.