



## Linksys Phone Adapter Configuration

[Info](#) | [System](#) | [SIP](#) | **Provisioning** | [Regional](#) | [Line 1](#) | [PSTN Line](#) | [User 1](#) | [PSTN User](#) | [User Login](#) | [basic](#) | [advanced](#)

### Configuration Profile

Provision Enable:	yes ▼	Resync On Reset:	yes ▼
Resync Random Delay:	2	Resync Periodic:	3600
Resync Error Retry Delay:	3600	Forced Resync Delay:	14400
Resync From SIP:	yes ▼	Resync After Upgrade Attempt:	yes ▼
Resync Trigger 1:			
Resync Trigger 2:			
Resync Fails On FNF:	yes ▼		
Profile Rule:	/spa\$PSN.cfg		
Profile Rule B:			
Profile Rule C:			
Profile Rule D:			
Log Resync Request Msg:	\$PN \$MAC -- Requesting resync \$SCHEME://\$SERVIP:\$PORT\$PATH		
Log Resync Success Msg:	\$PN \$MAC -- Successful resync \$SCHEME://\$SERVIP:\$PORT\$PATH		
Log Resync Failure Msg:	\$PN \$MAC -- Resync failed: \$ERR		
Report Rule:			

### Firmware Upgrade

Upgrade Enable:	yes ▼	Upgrade Error Retry Delay:	3600
-----------------	-------	----------------------------	------

Downgrade Rev Limit:

Upgrade Rule:

Log Upgrade Request Msg: \$PN \$MAC -- Requesting upgrade \$SCHEME://\$SERVIP:\$PORT\$PATH

Log Upgrade Success Msg: \$PN \$MAC -- Successful upgrade \$SCHEME://\$SERVIP:\$PORT\$PATH -- \$ERR

Log Upgrade Failure Msg: \$PN \$MAC -- Upgrade failed: \$ERR

### General Purpose Parameters

GPP A:

GPP B:

GPP C:

GPP D:

GPP E:

GPP F:

GPP G:

GPP H:

GPP I:

GPP J:

GPP K:

GPP L:

GPP M:

GPP N:

GPP O:

GPP P:

Undo All Changes

Submit All Changes

[User Login](#) [basic](#) | advanced

Copyright © 2003-2005 Sipura Technology. All Rights Reserved.