



A Division of Cisco Systems, Inc.

Linksys Phone Adapter Configuration

[Info](#) |
 [System](#) |
 SIP |
 [Provisioning](#) |
 [Regional](#) |
 [Line 1](#) |
 [PSTN Line](#) |
 [User 1](#) |
 [PSTN User](#) |
 [User Login](#) |
 [basic](#) |
 advanced

SIP Parameters

Max Forward:	70	Max Redirection:	5
Max Auth:	2	SIP User Agent Name:	\$VERSION
SIP Server Name:	\$VERSION	SIP Reg User Agent Name:	
SIP Accept Language:		DTMF Relay MIME Type:	application/dtmf-relay
Hook Flash MIME Type:	application/hook-flash	Remove Last Reg:	no ▼
Use Compact Header:	no ▼	Escape Display Name:	no ▼
RFC 2543 Call Hold:	yes ▼	Mark All AVT Packets:	yes ▼

SIP Timer Values (sec)

SIP T1:	.5	SIP T2:	4
SIP T4:	5	SIP Timer B:	32
SIP Timer F:	32	SIP Timer H:	32
SIP Timer D:	32	SIP Timer J:	32
INVITE Expires:	240	ReINVITE Expires:	30
Reg Min Expires:	1	Reg Max Expires:	7200
Reg Retry Intvl:	30	Reg Retry Long Intvl:	1200

Response Status Code Handling

SIT1 RSC:

SIT3 RSC:

Try Backup RSC:

SIT2 RSC:

SIT4 RSC:

Retry Reg RSC:

RTP Parameters

RTP Port Min: 16384

RTP Packet Size: 0.030

RTCP Tx Interval: 0

Stats In BYE: no ▼

RTP Port Max: 16482

Max RTP ICMP Err: 0

No UDP Checksum: no ▼

SDP Payload Types

NSE Dynamic Payload: 100

INFOREQ Dynamic Payload:

G726r24 Dynamic Payload: 97

G726r40 Dynamic Payload: 96

NSE Codec Name: NSE

G711u Codec Name: PCMU

G726r16 Codec Name: G726-16

G726r32 Codec Name: G726-32

G729a Codec Name: G729a

G723 Codec Name: G723

AVT Dynamic Payload: 101

G726r16 Dynamic Payload: 98

G726r32 Dynamic Payload: 2

G729b Dynamic Payload: 99

AVT Codec Name: telephone-event

G711a Codec Name: PCMA

G726r24 Codec Name: G726-24

G726r40 Codec Name: G726-40

G729b Codec Name: G729ab

NAT Support Parameters

Handle VIA received: no ▼

Insert VIA received: no ▼

Substitute VIA Addr: no ▼

STUN Enable: no ▼

STUN Server:

EXT RTP Port Min:

Handle VIA rport: no ▼

Insert VIA rport: no ▼

Send Resp To Src Port: no ▼

STUN Test Enable: no ▼

EXT IP:

NAT Keep Alive Intvl: 15

Undo All Changes

Submit All Changes

[User Login](#) [basic](#) | advanced

Copyright © 2003-2005 Sipura Technology. All Rights Reserved.