



A Division of Cisco Systems, Inc.

Linksys Phone Adapter Configuration

[Info](#) |
 [System](#) |
 [SIP](#) |
 [Provisioning](#) |
 [Regional](#) |
 [Line 1](#) |
 [PSTN Line](#) |
 User 1 |
 [PSTN User](#) |
 [User Login](#) |
 [basic](#) |
 advanced

Call Forward Settings

Cfwd All Dest:

Cfwd Busy Dest:

Cfwd No Ans Dest:

Cfwd No Ans Delay: 20

Selective Call Forward Settings

Cfwd Sel1 Caller:

Cfwd Sel1 Dest:

Cfwd Sel2 Caller:

Cfwd Sel2 Dest:

Cfwd Sel3 Caller:

Cfwd Sel3 Dest:

Cfwd Sel4 Caller:

Cfwd Sel4 Dest:

Cfwd Sel5 Caller:

Cfwd Sel5 Dest:

Cfwd Sel6 Caller:

Cfwd Sel6 Dest:

Cfwd Sel7 Caller:

Cfwd Sel7 Dest:

Cfwd Sel8 Caller:

Cfwd Sel8 Dest:

Cfwd Last Caller:

Cfwd Last Dest:

Block Last Caller:

Accept Last Caller:

Speed Dial Settings

Speed Dial 2:

Speed Dial 3:

Speed Dial 4:

Speed Dial 5:

Speed Dial 6:

Speed Dial 7:

Speed Dial 8:

Speed Dial 9:

Supplementary Service Settings

CW Setting: yes ▼
 Block ANC Setting: no ▼
 CID Setting: yes ▼
 Dist Ring Setting: yes ▼
 Message Waiting: no ▼

Block CID Setting: no ▼
 DND Setting: no ▼
 CWCID Setting: yes ▼
 Secure Call Setting: no ▼

Distinctive Ring Settings

Ring1 Caller: Ring2 Caller:
 Ring3 Caller: Ring4 Caller:
 Ring5 Caller: Ring6 Caller:
 Ring7 Caller: Ring8 Caller:

Ring Settings

Default Ring:	1 ▼	Default CWT:	1 ▼
Hold Reminder Ring:	8 ▼	Call Back Ring:	7 ▼
Cfwd Ring Splash Len:	0	Cblk Ring Splash Len:	0
VMWI Ring Splash Len:	0	VMWI Ring Policy:	New VM Available ▼
Ring On No New VM:	no ▼		

Undo All Changes

Submit All Changes

[User Login](#) | [basic](#) | advanced